


FRAME
Mass-dyed thermoplastic technopolymer

SEAT
Fabric-covered polyurethane

4182
Embossed fabric




Fire tested version
IT UNI 9175; EN1021 fire reaction test class 1 IM ministerial certification M118482D011M00018
US - California Standard TB 117 - UK Standard BS 7176 Medium Hazard - S.I. 1324




In order to better satisfy the needs of common areas, Clap is also available in a personalised version with fabrics provided by the client, for orders of at least 4 items.

Dimensions of customised fabric to cover a single piece: 140x125 cm.



4180/4182	1	6.15	0.161	54X49X61
	1	3.97	0.120	51X51X46




STRUCTURE
Recycled and recyclable batch-dyed thermoplastic technopolymer



SEAT
Rubelli Quatrefoil® design by Luke Edward Hall fabric



FRAME
Batch-dyed thermoplastic technopolymer, recycled and recyclable for the black version



SEAT
AquaClean® fabric



4187/4188	1	6.15	0.161	54X49X61
	1	3.97	0.120	51X51X46



EN 1022:2005	Compliant
EN 16139:2013	Compliant
EN 1728:2012	level attained
6.4	(maximum level) L2
6.5	(maximum level) L2
6.6	(maximum level) L2
6.10	(maximum level) L2
6.11	(maximum level) L2
6.15	(maximum level) L2
6.16	(maximum level) L2
6.17	(maximum level) L2
6.18	(maximum level) L2
6.20	(maximum level) L2
6.24	(maximum level) L2
6.25	(maximum level) L2
6.26	(maximum level) L2

EN 1022:2005	Compliant
EN 16139:2013	Compliant
EN 1728:2012	level attained
6.4	(maximum level) L2
6.5	(maximum level) L2
6.6	(maximum level) L2
6.10	(maximum level) L2
6.11	(maximum level) L2
6.15	(maximum level) L2
6.16	(maximum level) L2
6.17	(maximum level) L2
6.18	(maximum level) L2
6.20	(maximum level) L2
6.24	(maximum level) L2
6.25	(maximum level) L2
6.26	(maximum level) L2