

NEW PRODUCT!



**9390 / 9391 / 9386 / U9386  
Z9386 / 9385 / U9385 / Z9385**

B4/crystal	
Gl/yellow	
FU/smoke	



		class of insulation	direct mounting	degree of protection	power voltage	max. wattage	unit weight kg.
<b>9390</b>				IP 20	220-240	22W LED	2.700
<b>9391</b>				IP 20	120	19W LED	2.700
		diameter Ø	height diffuser	length min÷max			
		33	27	38÷232			
<b>9386</b>				IP 20	220-240	22W LED	2.700
<b>U9386 Z9386</b>				IP 20	120	19W LED	2.700
		Ø diameter	height				
		33	28				
<b>9385 B9385 WITH DIMMER</b>				IP 20	220-240	22W LED	3.140
<b>U9385 Z9385 ON/OFF</b>				IP 20	120	19W LED	3.140
		Ø diameter	height				
		33	53				
<b>Material</b>	transparent or mass-dyed thermoplastic technopolymer						
<b>Frame:</b>	Polished or painted die-cast aluminium						
<b>packaging</b>	quantity	weight kg.	volume m <sup>3</sup>	dimension			
<b>9390 / 9391</b>	1	4.100	0.050	39X33X39			
<b>9386 / U9386 / Z9386</b>	1	4.080	0,054	39X39X33			
<b>9385 / U9385 / Z9385</b>	1	4.720	0.085	39X55X44			