




TYPE	Pendant		
CONSTRUCTION	Hand blown frosted glass Powder coated aluminum body Polyester cord		
SPECIFICATIONS	Source: LED lamp provided (G9 base) Power consumption: 4.5W Lumen output: 319Im		
	Colour temperature: 2700K included * 3000K available upon request Colour rendering index: ≥ 90 CRI standard Expected lifetime: ≥ 25 000h		
CONTROL	Refer to our recommended list of dimmer models		
CORD LENGTH	108" / 274 cm		
STAINLESS STEEL CABLE	96" / 244 cm		
WEIGHT	3.5lb / 1.6kg		
CERTIFICATIONS	© C € vKoHS Ø IP20		
WARRANTY	2 years		





FINISH WH ΒU MB BG Textured Textured Textured Textured Textured Textured black white midnight blue beige burgundy blue Textured Textured terracotta green CORD (*CORDS ONLY AVAILABLE IN BLACK OR WHITE VINYL FOR AUSTRALIA) WH ΒE BG

LAMP ANATOMY



NOTES

Black

GN Green

- Must be installed by an electrician

White

- Not protected against liquids (refer to IP20)
- Additional charges for modifications or for special orders

Midnight

blue

Blue

Beige

Burgundy


- Please refer to maintenance sheet on our website for cleaning instructions
- Ceiling anchor not meant for slanted ceilings (available upon request)

		Example	Fill with your selection
COLLECTION	PARC Prc	PRC	PRC
MODEL	02	02	02
POSITION	A Anchor NA No anchor	A	
FINISH	BK Textured Black WH Textured White MB Textured Midnight Blue BE Textured Blue BG Textured Beige BU Textured Burgundy GN Textured Green TC Textured Terracotta CC Custom colour*	вк	
CORD	BK Black WH White MB Blue BE Blue BG Beige BU Burgundy GN Green CC Custom colour*	вк	
CANOPY AND ANCHOR	BK Textured Black WH Textured White MB Textured Midnight Blue BE Textured Blue BG Textured Beige BU Textured Burgundy GN Textured Green TC Textured Terracotta CC Custom colour*	вк	
FULL SKU		PRC02ABKBKBK	
		NOTES	

^{*}Custom colour available upon request. Material library on website.



ТҮРЕ	Pendant		
CONSTRUCTION	Hand blown frosted glass Powder coated aluminum body Polyester cord		
SPECIFICATIONS	Source: LED lamp provided (G9 base) Power consumption: 2x 4.5W Lumen output: 638Im		
	Colour temperature: 2700K included * 3000K available upon request Colour rendering index: ≥ 90 CRI standard Expected lifetime: ≥ 25 000h		
CONTROL	Refer to our recommended list of dimmer models		
CORD LENGTH	108" / 274 cm		
STAINLESS STEEL CABLE	96" / 244 cm		
WEIGHT	3.5lb / 1.6kg		
CERTIFICATIONS	¢∰us (€ v⊀oHs ⊘ IP20		
WARRANTY	2 years		



^{*}dimensions are approximate and may vary slightly

FINISH wн BG Textured Textured Textured Textured Textured Textured black white midnight blue beige burgundy blue Textured Textured terracotta green CORD (*CORDS ONLY AVAILABLE IN BLACK OR WHITE VINYL FOR AUSTRALIA)

ΒE

Blue

Midnight

blue


ΒU

Burgundy

BG

Beige

LAMP ANATOMY



NOTES

ΒK

GN Green

Black

- Must be installed by an electrician

WH

White


- Not protected against liquids (refer to IP20)
 Additional charges for modifications or for special orders
- Please refer to maintenance sheet on our website for cleaning instructions
- Ceiling anchor not meant for slanted ceilings (available upon request)

		Example	Fill with your selection
COLLECTION	PARC Prc	PRC	PRC
MODEL	03	03	03
BODY	BK Textured Black WH Textured White MB Textured Midnight Blue BE Textured Blue BG Textured Beige BU Textured Burgundy GN Textured Green TC Textured Terracotta CC Custom colour*	ВК	
CORD	BK Black WH White MB Blue BE Blue BG Beige BU Burgundy GN Green CC Custom colour*	ВК	
CANOPY AND ANCHOR	BK Textured Black WH Textured White MB Textured Midnight Blue BE Textured Blue BG Textured Beige BU Textured Burgundy GN Textured Green TC Textured Terracotta CC Custom colour*	ВК	
FULL SKU		PRC03BKBKBK	
		NOTES	

^{*}Custom colour available upon request. Material library on website.



ТҮРЕ	Pendant		
CONSTRUCTION	Hand blown frosted glass Powder coated aluminum body Polyester cord		
SPECIFICATIONS	Source: LED lamp provided (G9 base) Power consumption: 2x 4.5W Lumen output: 638Im		
	Colour temperature: 2700K included * 3000K available upon request Colour rendering index: ≥ 90 CRI standard Expected lifetime: ≥ 25 000h		
CONTROL	Refer to our recommended list of dimmer models		
CORD LENGTH	108" / 274 cm		
STAINLESS STEEL CABLE	96" / 244 cm		
WEIGHT	3.5lb / 1.6kg		
CERTIFICATIONS	¢∰us (€ v⊀oHs ⊘ IP20		
WARRANTY	2 years		



^{*}dimensions are approximate and may vary slightly

FINISH wн BG Textured Textured Textured Textured Textured Textured black white midnight blue beige burgundy blue Textured Textured terracotta green CORD (*CORDS ONLY AVAILABLE IN BLACK OR WHITE VINYL FOR AUSTRALIA)

ΒE

Blue

Midnight

blue


ΒU

Burgundy

BG

Beige

LAMP ANATOMY



NOTES

ΒK

GN Green

Black

- Must be installed by an electrician

WH

White


- Not protected against liquids (refer to IP20)
 Additional charges for modifications or for special orders
- Please refer to maintenance sheet on our website for cleaning instructions
- Ceiling anchor not meant for slanted ceilings (available upon request)

		Example	Fill with your selection
COLLECTION	PARC Prc	PRC	PRC
MODEL	03	03	03
BODY	BK Textured Black WH Textured White MB Textured Midnight Blue BE Textured Blue BG Textured Beige BU Textured Burgundy GN Textured Green TC Textured Terracotta CC Custom colour*	ВК	
CORD	BK Black WH White MB Blue BE Blue BG Beige BU Burgundy GN Green CC Custom colour*	ВК	
CANOPY AND ANCHOR	BK Textured Black WH Textured White MB Textured Midnight Blue BE Textured Blue BG Textured Beige BU Textured Burgundy GN Textured Green TC Textured Terracotta CC Custom colour*	ВК	
FULL SKU		PRC03BKBKBK	
		NOTES	

^{*}Custom colour available upon request. Material library on website.




TYPE	Pendant			
CONSTRUCTION	Hand blown frosted glass Powder coated aluminum body Polyester cord			
SPECIFICATIONS	Source: LED lamp provided (G9 base) Power consumption: 3x 4.5W Lumen output: 957lm			
	Colour temperature: 2700K included * 3000K available upon request Colour rendering index: ≥ 90 CRI standard Expected lifetime: ≥ 25 000h			
CONTROL	Refer to our recommended list of dimmer models			
CORD LENGTH	108" / 274 cm			
STAINLESS STEEL CABLE	96" / 244 cm			
WEIGHT	3.5lb / 1.6kg			
CERTIFICATIONS	® (€ vfoHs 🙆 IP20			
WARRANTY	2 years			



^{*}dimensions are approximate and may vary slightly

FINISH WH BG ΒU Textured Textured Textured Textured Textured Textured midnight black white blue beige burgundy blue Textured Textured terracotta green CORD (*CORDS ONLY AVAILABLE IN BLACK OR WHITE VINYL FOR AUSTRALIA)






GN Green

NOTES

- Must be installed by an electrician
- Not protected against liquids (refer to IP20)
 Additional charges for modifications or for special orders
- Please refer to maintenance sheet on our website for cleaning instructions
- Ceiling anchor not meant for slanted ceilings (available upon request)

LAMP ANATOMY



		Example	Fill with your selection
COLLECTION	PARC Prc	PRC	PRC
MODEL	04	04	04
BODY	BK Textured Black WH Textured White MB Textured Midnight Blue BE Textured Blue BG Textured Beige BU Textured Burgundy GN Textured Green TC Textured Terracotta CC Custom colour*	вк	
CORD	BK Black WH White MB Blue BE Blue BG Beige BU Burgundy GN Green CC Custom colour*	вк	
CANOPY AND ANCHOR	BK Textured Black WH Textured White MB Textured Midnight Blue BE Textured Blue BG Textured Beige BU Textured Burgundy GN Textured Green TC Textured Terracotta CC Custom colour*	ВК	
FULL SKU		PRC04BKBKBK	
		NOTES	

 ${}^{\star}\text{Custom colour available upon request. Material library on website.}$

DIMMER LIST COMPATIBILITY FOR G9 LED BULBS - 120V

The dimming technology offering the best results is ELV (electronic low voltage) dimmers with reverse phase or trailing edge control.

DIMMER BRAND	MODEL	MAX LEVEL	MIN LEVEL	DIMMING PROTOCOL
LUTRON - MAESTRO	MAELV-600	100%	0%	Phase Cut
LUTRON - SKYLARK	SELV-300P	100%	0%	Phase Cut
LUTRON - SKYLARK	SELV-300P	100%	0%	Phase Cut
LUTRON - SKYLARK	CTELV-303P	100%	0%	Phase Cut
LUTRON - DIVA	DVELV-300P	100%	0%	Phase Cut
LEGRAND - ADORNE	TRUE UNIVERSAL	100%	30%	Phase Cut

DIMMER LIST COMPATIBILITY FOR G9 LED BULBS - 230V

Phase cut dimming (leading edge or trailing edge**)

DIMMER BRAND	MODEL	MAX LEVEL	MIN LEVEL	DIMMING PROTOCOL
VARILIGHT	V-PRO	100%	2%	Phase Cut
LEGRAND - NILOÉ	3 996 35	87%	15%	Phase Cut
NIKO	310-0280X	94%	5%	Phase Cut
NIKO	310-0190X	100%	1%	Phase Cut

^{*}Other dimmers can yield good results and we recommend conducting your own test before final installation.

Some dimmers require a minimum load, check specifications.

 ${}^{\star} Other\ dimmers\ that\ specify\ LED\ lamp\ compatibility\ may\ operate\ without\ issue.$

We recommend conducting your own test before final installation.

**Leading edge is also known as TRIAC or Forward Phase.

Trailing edge is also known as ELV or Reverse Phase.